

ATM03 | Wet Location Linear Luminaire

Overview

The ATM03 brings refined architectural style to the most demanding environments, delivering clean, consistent light with flexible options and style while boasting sealed, IP65 certified housing.

Part #:

ATM03 | Wet Location Linear

Lumens:

High Lumen:
1,500 Lm
12.5 W per ft.

Med Lumen:
1,200 Lm per ft.
10 W per ft.

Low Lumen:
900 Lm per ft.
7.5 W per ft.

Color:

CCT:
3000K
3500K
4000K

CRI:
80

Voltage:

Standard:
120-277 V

Dimming:

Standard:
0-10V - 5%

Lifetime:

Standard:
L70 > 100,000 Hrs.

Operating Temperature:

Standard:
-4°F to 104°F

Finishes:

Midnight RAL 9005	Pearly Gate RAL 9016	Silver Gray RAL 7045
----------------------	-------------------------	-------------------------

Custom color available*

*All custom color requests must be call to order and will affect leadtimes.
Accommodation for RAL color code is available.



ATMOS (ATM03)

Wet Location Linear - Direct

Features:

Dependable and beyond.
4FT standard, with options for continous runs.


Bend the light to your whims
Specific lumen outputs, 3 CCT + 80 CRI standard.

Specification grade construction
Sealed extruded aluminium housing and die cast endcaps. No shortcuts on material.



Mounting:

Pendant Mount



Surface Mount:




Wall Mount:



Dimensions:

Model	L	W	H
ATM03	48"	3.15"	3.70"





Type:	Project:	Submitted by:	Date:
Ordering information:			

ATM03 | Wet Location Linear Luminaire

Example: ATM03 D IF4 SM 1200 D 840 BL

Ordering Guide:
Use the buttons below to build out a product number.

Select one option per numbered section. if a preferred option is not here, please contact your local SPRNG representative for more information.

Linear Body				Output and color			
1 Series	2 Light Style	3 Length	4 Mounting	5 Output	6 Voltage	7 Dimming	8 CCT/CRI
ATM03 ATM03 - Wet Location Linear	D Direct - Downlight	IF4 4FT Individual Fixture CR Continuous Run (Please specify in increments of 4FT).	P Pendant mount (2" Stem standard). SM* Surface mount to dry wall. WM Wall mount. *Note: Only compatible with Dry wall ceilings.	1500 1,500 Lumens / 12.5 Watts per FT 1200 1,200 Lumens / 10 Watts per FT 900 900 Lumens / 7.5 Watts per FT	BLANK 120V-277V	D 0-10V - 5%	830 80 CRI - 3000K 835 80 CRI - 3500K 840 80 CRI - 4000K

Finishing

9 Finish

BL
Midnight black - RAL9005

WH
Pearly gate white - RAL9016

SG**
Shining silver gray - RAL7045

RAL color code

**Must be call to order and will affect leadtimes.

Performance Data

	3000K (80 CRI)	3500K (80 CRI)	4000K (80 CRI)
Lumens Per FT	1,500 Lm/FT	1,625 Lm/FT	1,575 Lm/FT
Watts per FT	12.5W/FT	12.5W/FT	12.5W/FT
Lumens per Watt	120 Lm/W	130 Lm/W	126 Lm/W

Electrical Data:

Size	Driver Current (mA)	Nominal Power (W)	Input Voltage (V)	Current (Amps)
4FT	1050	50	120	0.42
			208	0.24
			240	0.21
			277	0.18